

B570

WHEEL FELLER BUNCHER



ENHANCED TRAVEL & SAW RECOVERY.

The patented PowerDirect Plus system optimizes performance by focusing power where the operator demands. The hydraulic pumps are oversized providing greater overall capacity and improved travel power and saw recovery.



ROCK SOLID STABILITY.

The patented transverse mounted engine design and low center of gravity provide rock solid stability. Superior stability delivers market leading cut and carry capability to build larger, easy to reach bundles improving skidder efficiency.



APPLICATION VERSATILITY.

The balance of a short wheelbase, power, stability and agility provides superior application versatility allowing seamless transitions from 1st thinnings to final fell applications. Versatility maximizes long term value as markets fluctuate.



OPERATOR COMFORT.

A quiet and spacious cab with a powerful HVAC system and rear view camera keep operators comfortable and productive. The premium seat with more leg room near the joystick mounts and overall machine balance provide a superior ride.



EXCELLENT SERVICEABILITY.

Pressurized engine, hydraulic and after treatment compartments keep debris out of the machine reducing down time for clean out. Ground level fuel fill, electric hydraulic oil fill pump and superior engine access deliver excellent serviceability.



GREATER DURABILITY & RELIABILITY.

The field proven cooling system keeps the engine and hydraulics cool, extending component life. Robust frames with integrated steering cylinder mounts and field proven hitch for nearly 20 years are built for the harshest applications.

B570 SPECIFICATIONS

Engine Model	Cat® 7.1 ACERT™	Wheelbase	110.0" 2794 mm	Ground Clearance	19.4" 493 mm
Gross Power	203 hp 151 kW	Fuel Capacity	81.6 gal 309 L	Transport Width	9' 7" 2.92 m
Engine Speed	1880 rpm	DEF Capacity	5.0 gal 19 L	Transport Height	10' 5" 3.17 m
Weight	39,120 lb 17 744 kg	Hydraulic System Capacity	64.2 gal 243 L	Transport Length	24' 9" 7.55 m

Base configuration includes 28L-26 16PR Tires and 232 High Capacity Bunching Saw. Weight add 1,720 lb (790 kg) for 30.5L-32 tires, 2,560 lb (1161 kg) for 30.5L-32 2X Ring tires, 1,720 lb (780 kg) for 67-34 tires. Height and ground clearance add 4.0" (10.2 cm) for 30.5L-32 tires, 1.1" (2.8 cm) for 67-34 tires.

POWERTRAIN

- Cat C7.1 ACERT engine certified to EPA Tier 4 Final
- Primary and secondary fuel filters, including water separator
- Electric fuel priming pump
- Electric fuel transfer pump
- Centrifugal air pre-cleaner
- 2-Stage air cleaner
- Cross-flow cooling system with side by side cores
- Swing out air condition condenser and fuel cooler
- Hydraulically driven, on demand reversing cooling fan
- Electronically driven, reversing pressurizing fan
- 2-Speed, manually shifted transmission
- Cat HD axles, approved for odd size dual tires up to 30.5L-32 with 24.5L-32 and wide tires up to 73-44
- Momentary front differential lock
- On/off rear differential lock
- Heavy-duty driveshafts
- Lubed for life universal joints
- Spring applied, hydraulically released parking brake

OPERATING ENVIRONMENT

- Enclosed OPS/FOPS/ROPS certified cab
- Reverse slope 3-piece windshield
- High capacity HVAC system
- Pressurized water tank
- Air suspension seat with harness seat belt
- Joystick steering controls
- Joystick gather arm(s) controls
- Foot pedal gather arm(s) controls ready only
- AM/FM/Bluetooth Radio
- Rear view camera
- 24-volt to 12-volt converter and 2 12-volt power ports
- 2 Beverage holders
- Advanced Operator Controls
- Operator control adjustability
- Terrain Selection Mode
- Creep Mode
- Road Steer Mode
- Computerized Monitoring System

SALES AND SERVICE

Sold and serviced exclusively through Weiler Forestry dealers worldwide

WEILERFORESTRY.COM

HYDRAULICS

- PowerDirect Plus System
- Load-sense hydraulics
- Variable displacement pumps
- High performance, multi-functioning main control valve
- Dual inline, spin on return filters
- Electric hydraulic oil fill pump

ELECTRICAL

- 130 ampere alternator
- 24-volt electric system with 2 12-volt batteries
- Main disconnect switch with Diesel Exhaust Fluid (DEF) purge indicator light
- 6 halogen working lights
- Product Link™ Ready

OTHER STANDARD EQUIPMENT

- Heavy-duty double walled box section frames
- Dual tapered roller bearing upper and lower center hitch
- Pins, Chrome plated lift arm and tilt pins
- Ecology drains (engine oil, engine coolant, hyd tank, fuel tank, axles)
- Tilt Cab
- Pressurized engine, hydraulic and CEM compartments
- Ground level fuel fill
- Remote mounted test ports
- Single side engine service
- S-O-S sampling ports

OPTIONAL EQUIPMENT

- 221 Center Post Felling Saw - 22.7" (576 mm)
- 232 High Capacity Bunching Saw - 22.6" (573 mm)
- 222SC Side Cut Felling Saw - 22.0" (560 mm)
- 28L x 26 NOAW Tires - Overall Width 9' 2" (2.79 m)
- 28L x 26 Tires - Overall Width 9' 7" (2.92 m)
- 30.5L x 32 NOAW Tires - Overall Width 9' 9" (2.98 m)
- 30.5L x 32 Tires - Overall Width 10' 4" (3.16 m)
- 30.5L x 32 2X Ring Tires - Overall Width 9' 9" (2.98 m)
- 67 x 34 Tires - Overall Width 10' 7" (3.22 m)

WARRANTY

12 months standard. Extended warranty available