

OPTIONS AND ACCESSORIES KIT GUIDE FOR SMALL WHEEL LOADERS

MODEL (SERIAL NUMBER PREFIX):

926M (LTE, W5L), 930M (F5K, HEY, J5K, KTG), 938M (J3R, P5K) 924K (PWR), 930K (RHN), 938K (SWL) 924K (HJF, KW4, SNZ), 930K (EYE, FRK, P3K), 938K (REP, W8K, XXT)



Option/AccessoryPage Nu	ımber
COMFORT AND CONVENIENCE	3-4
Cell Phone Holder	3
Forward-Neutral-Reverse (FNR) Shift Lever	3
Radio, Digital Audio Broadcasting (DAB)	4
Two Lever Loader Controls	4
EMISSIONS AND REGULATIONS	5-6
Fuel Ecology Drain	5
License Plate Mounting Bracket	5
Roading Lights, Halogen	6
Roading Lights, LED	6
Troduing Lights, LLD	Ü
SAFETY AND VISIBILITY	7-16
Auxiliary Halogen Work Lights	7
Auxiliary LED Work Lights	7
Lighting, HID	8
LED Strobe Warning Beacon	8
Front View Camera	9
High Visibility for Handrails and Steps	9
LED Engine Enclosure Lights	10
Rear Object Detection Radar	10
Rear View Camera	11
Rear Vision Monitor	11
Secondary Display, Touch Screen	12
Seat Belt, Four Point for Deluxe Seat	13
Seat Belt, Four Point for Premium Seat	13
Service Tie Off	14
Tire Pressure Monitor	15
Windshield Access Steps	16
GUARDING	17-26
Crankcase Guard	17
Driveshaft Guard	17
Fenders, Extended Cover	18
Fenders, Roading	18
Mud Flaps, Full Cover	19
Fender Deflectors, Waste	19
Hitch Guard	20
Light Guards, Front	20
Light Guards, Rear	21
Polycarbonate Front Windshield	21
Windshield Guard	22
Power Train Lower Guard	22
Power Train Side Guard	23
Rear Radiator Guard	23
Steering Cylinder Guard	24
Tilt Cylinder Guard High Lift	ar.
High LiftStandard Lift	25 26
OLGITUGEU F.III	70

Option/AccessoryPage No.	ımber
MAINTENANCE AND IMPROVEMENT	27-28
Cab Air Filter (RESPA)	27
Precleaner	27
Fuel Door	28
PERFORMANCE AND PRODUCTIVITY	29-52
Alternator, Heavy Duty	29
Autolube	30
Axle Breather	31
Block Heater – 120V	31
Block Heater – 240V	32
Ether Aid	32
Heavy Duty Starting	33
Cat Production Measurement (CPM)	34
CPM Printer	35
Counterweight, Heavy	36
Counterweight, Aggregate	36
Dual Mode Steering (Quick Steer)	37
Product Link Elite Network Manager	38
Quick Coupler Disconnects	39
Quick Coupler, Cast Fusion	40
Quick Coupler, Fabricated Fusion	41
Quick Coupler, Cast ISO	42
Quick Coupler, ISO	43
Coupler Ready	44
Fusion Hook, Flat Back	45
Fusion/IT Adapter	45
Reversing Fan	46
Ride Control	47
Fourth Valve Auxiliary Hydraulic System	48
Third and Fourth Valve Auxiliary Hydraulic System,	
Standard Lift	49
Third Function Coupler Jumper Lines	50
Third Valve Auxiliary Hydraulic System	
High Lift	51
Standard Lift	52
SECURITY	54
Machine Security System (MSS)	54

COMFORT AND CONVENIENCE

Cell Phone Holder


The spring-loaded phone holder features an "X" design that expands and contracts to provide a perfect fit for your device. Holder is made of powder-coated, marine-grade aluminum, stainless steel components, and high-strength composite for durability.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	612-6230	0.5 Hour
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

Forward-Neutral-Reverse (FNR) Shift Lever

Provides an FNR shifter lever, wiring harness, mounting bracket and templates to modify the existing bracket and covers to install the shifter on the left side of the steering column. The multi-function stalk switch is relocated to the right side of the column.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	471-7009*	Recommended Dealer Install
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		motun

^{*}This kit has software enabled features that must be activated by a Cat® dealer. Requires Cat Electronic Technician (ET) to complete installation of this kit.

Radio, Digital Audio Broadcasting (DAB)


Provides an AM/FM radio which includes DAB interface. Includes Bluetooth® interface, a microphone and auxiliary inputs for powering MP3 players, etc. DAB is not broadcasted in all regions.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	494-7996	0.25 Hour

Two Lever Loader Controls

Provides single axis lift and tilt loader control levers for use with two valve hydraulic system. Includes control levers, console mounted Forward-Neutral-Reverse (FNR) switch, differential lock switch, horn switch, console, harness, brackets, and hardware.




Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	457-0939	Recommended Dealer Install
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		motun

EMISSIONS AND REGULATIONS

Fuel Ecology Drain

Provides an ecology drain plug and tube for the fuel tank.






Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	363-4245	0.5 Hour
924K, 930K, 938K	HJF, KW4, EYE, P3K, W8K, XXT		

License Plate Mounting Bracket


An illuminated license plate holder that mounts to the rear door.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	374-5865	0.25 Hour
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

Roading Lights, Halogen

Provides low/high beam halogen lights for driving on the left or right side of the road.




Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	363-0277* 363-0278**	0.25 Hour
924K, 930K, 938K	PWR, RHN, SWL	303-02/6***	

^{*}For countries that drive on the left side of the highway.
**For countries that drive on the right side of the highway.

Roading Lights, LED

Provides low/high beam LED lights for driving on the left or right side of the road.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	582-8942* 582-8941**	0.25 Hour

^{*}For countries that drive on the left side of the highway.

^{**}For countries that drive on the right side of the highway.

SAFETY AND VISIBILITY

Auxiliary Halogen Work Lights

Provides two (2) additional forward facing, cab mounted halogen (70W) wide flood work lights, and two (2) rear facing cab mounted halogen (70W) wide flood work lights.







Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	374-5868	1.0 Hour
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

Auxiliary LED Work Lights

Provides two (2) additional forward facing, cab mounted LED (2100 lm) low beam work lights, two (2) rear facing, cab mounted LED (850 lm) wide flood work lights. LED lighting provides brighter lighting and longer life.








Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	452-0853	1.0 Hour
924K, 930K, 938K	KW4, SNZ, FRK, P3K, REP, W8K		

Lighting, High Intensity Discharge (HID)

Kit provides two (2) additional forward-facing HID work lights, and two (2) additional rear facing, cab mounted, halogen work lights.








Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	374-5869	1.0 Hour
924K, 930K, 938K	HJF, SNZ, EYE, FRK, REP, XXT		

LED Strobe Warning Beacon

Provides hard mounted LED strobe beacon on hinged (breakaway) bracket mounted to the rear of the cab structure.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	370-7008	0.25 Hour
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

Front View Camera

Includes camera, display, harness, brackets and hardware to mount a forward-facing camera system. The forward-facing camera is mounted to an external breakaway bracket in the top left corner of cab. The display is mounted in the upper left corner of the cab and replaces an internal mirror. The forward camera may be required for local European Union (EU) requirements. Consult your Cat dealer for additional information and reference product bulletin TEJB9977.







Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	582-1425*	Recommended Dealer
924K, 930K, 938K	KW4**, SNZ, FRK, P3K**, REP, W8K**	30Z-14Z3"	Install


^{*}Requires Cat Electronic Technician (ET) to complete installation of this kit.

^{**}Applicable only to machines within the following serial number range:

Model	Serial Number Range
924K	KW402100-KW499999
930K	P3K01000-P3K99999
938K	W8K02000-W8K99999

High Visibility for Handrails and Steps

This kit provides high visibility reflective decals for the left-hand and right-hand handrails and steps. Also includes decals for the handrails on the inside of the cab door.






Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	615-1920	1.5 Hours
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT	013-1320	1.5 110413

LED Engine Enclosure Lights

Provides three (3) LED engine enclosure lights to illuminate the way for checking oil and coolant levels along with refueling the machine in dark conditions.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE*, W5L, F5K, HEY, J5K, KTG, J3R, P5K	463-3795	Recommended Dealer
924K, 930K, 938K	KW4, SNZ, FRK, P3K, REP, W8K		Install

^{*}Applicable only to machines within serial number range LTE00001-LTE06549.

Rear Object Detection Radar

Provides a rear door mounted radar system to warn the operator visually and audibly of close-by objects to the rear of the machine. Requires secondary display and rear camera. This kit is not available in all regions. Consult your Cat dealer.






Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	619-6725*	Recommended Dealer Install
924K, 930K, 938K	KW4, SNZ, FRK, P3K, REP, W8K		IIISLAII

^{*}Requires Cat Electronic Technician (ET) to complete installation of this kit.

Rear View Camera

Provides rear view camera that mounts to rear door. Includes camera, mounting bracket, harness, and hardware. Requires secondary display.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	463-3793*	Recommended Dealer Install
924K, 930K, 938K	KW4, SNZ, FRK, P3K, REP, W8K		iiistäli

^{*}This kit has software enabled features that must be activated by a Cat dealer. Requires Cat Electronic Technician (ET) to complete installation of this kit.

Rear Vision Monitor

Provides a dedicated rear vision monitor mounted high on the right front interior cab post, when a rear view is desired to be on permanent display. Can be used with any NTSC or PAL camera located elsewhere on the machine.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	372-1949*	Recommended Dealer Install
924K, 930K, 938K	PWR, RHN, SWL		IIIStali

^{*}This kit has software enabled features that must be activated by a Cat dealer. Requires Cat Electronic Technician (ET) to complete installation of this kit.

Secondary Display, Touch Screen

Provides a secondary touch screen display which allows real time adjustments to rimpull, creeper speed, 3rd function flow, throttle lock, and duals as a rear camera display (camera not included).





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	494-7956*	Recommended Dealer
924K, 930K, 938K	KW4**, SNZ, FRK, P3K**, REP, W8K**	494-7900"	Install

^{*}Requires Cat Electronic Technician (ET) to complete installation of this kit.

 $[\]ensuremath{^{**}}\xspace$ Applicable only to machines within the following serial number range:

Model	Serial Number Range
924K	KW401100-KW499999
930K	P3K00500-P3K99999
938K	W8K00900-W8K99999

Seat Belt, Four Point for Deluxe Seat

Provides harness and hardware for installation of four-point seat belts on the deluxe seat.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	552-8381*	4.0 Hours
924K, 930K, 938K	SNZ, FRK, REP		

^{*}Machine must have deluxe seat, part number, 563-5967, installed. The part number provided is for reference only. Individual parts must be ordered. Please consult your Cat dealer for parts list.

Seat Belt, Four Point for Premium Seat

Provides harness and hardware for installation of four-point seat belts on the premium seat.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	552-8380*	2.0 Hours
924K, 930K, 938K	SNZ, FRK, REP		

^{*}Machine must have premium seat, part number, 563-5968, installed.

Service Tie Off


Provides a service tie off on exterior of the left rear corner of the cab, allowing for safety harness tethering. This is a weld-on dealer attachment.




Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K	PWR	502-4860	Recommended Dealer Install
924K, 930K, 938K	KW4, SNZ, EYE, FRK, P3K, REP, W8K		motun

Tire Pressure Monitor

Includes four sensors that mount to the valve stem of each tire along with a receiver module that monitors both pressure and temperature in each tire. Tire pressure and temperature information are shared with the operator via the secondary display. Warnings are provided via the secondary display and through Unified Fleet if pressure is outside of a configurable target range. Software license for Cat Tire Pressure Monitoring (TPM) will be a separate charge. Requires secondary touch screen display. Requires 518-3231 Software, for permanent activation.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE**, W5L**, F5K**, J5K**, KTG**, J3R**, P5K**	494-7947*	1.0 Hour
924K, 930K, 938K	KW4**, SNZ, FRK, P3K**, REP, W8K**		


^{*}This kit has software enabled features that must be activated by a Cat dealer. Requires Cat Electronic Technician (ET) to complete installation of this kit.

^{**}Applicable only to machines within the following serial number range:

Model	Serial Number Range
926M	LTE03500-LTE99999, W5L00100-W5L99999
930M	F5K00110-F5K99999, J5K00115-J5K99999, KTG03000-KTG99999
938M	J3R03650-J3R99999,P5K00100-P5K99999
924K	KW401100-KW499999
930K	P3K00500-P3K99999
938K	W8K00900-W8K99999

Windshield Access Steps

Provides right hand side front frame mounted steps and handrail to facilitate access for an operator to clean the front windshield.




Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	445-2010*	2.0 Hours
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

^{*}Welding may be required to complete install.

GUARDING

Crankcase Guard

Provides engine crankcase guard that mounts underneath the rear frame.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	374-5845	0.25 Hour
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

Driveshaft Guard

Provides drive shaft guard that mounts underneath the front frame.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M	LTE, W5L, F5K, HEY, J5K, KTG		
924K, 930K	PWR, RHN	374-5842	
924K, 930K	HJF, KW4, SNZ, EYE, FRK, P3K		0.5.110
938M	J3R, P5K		0.5 Hour
938K	SWL	374-5843	
938K	REP, W8K, XXT		

Fenders, Extended Cover

Provides yellow, non-metallic front fenders and extended coverage rear fenders. Kit converts standard fender to extended cover. Recommended for applications that include long load and carry.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M	LTE, W5L, F5K, HEY, J5K, KTG	374-5857	- 1.0 Hour
924K, 930K	PWR, RHN		
938M	J3R, P5K	374-5847	
938K	SWL		

Fenders, Roading

Provides yellow, non-metallic front fenders and extended coverage rear fenders to convert machine for roading on long load and carry applications. Drive shaft guard that mounts underneath the front frame.






Model	Serial Number Prefix	Part Number	Estimated Install Time
924K, 930K	HJF, KW4, SNZ, EYE, FRK, P3K	430-2921	1.0 Hour
938K	REP, W8K, XXT	430-2922	

Mud Flaps, Full Cover

Kit provides mud flaps for extended coverage to the front and rear tires. Kit converts extended cover fender group to full cover.








Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M	LTE, W5L, F5K, HEY, J5K, KTG	452-0859*	1.0 Hour
938M	J3R, P5K	452-0860*	

^{*}Not compatible with the Standard Fenders 366-8148.

Fender Deflectors, Waste

Provides yellow, metal front deflectors that provide protection to hitch, ladder, and cab from debris thrown up or stuck in the front tires.






Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	437-8603	0.5 Hour
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

Hitch Guard

Provides protection to hitch area of the rear frame, preventing debris from entering the frame, while allowing visibility to service points.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	433-2002	1.0 Hour
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

Light Guards, Front

Provides two (2) front light guards that mount over the headlights.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	374-5861*	0.5 Hour
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

^{*}Cannot be used when machine is equipped with certain regional roading regulations packages. Contact your Cat dealer for further information.

Light Guards, Rear

Kit provides two (2) rear light guards that mount over the taillights.




Model	Serial Number Prefix	Part Number	Estimated Install Time
924K	HJF, SNZ, KW4	430-2924*	
930M	F5K, HEY, J5K, KTG		
930K	RHN	374-5863*	
930K	EYE, FRK, P3K		0.25 Hour
938M	J3R, P5K		
938K	SWL	374-5864*	
938K	REP, W8K, XXT		


^{*}Not compatible with the Heavy-Duty Rear Radiator Guard. Cannot be used when machine is equipped with certain regional roading regulations packages. Contact your Cat dealer for further information

Polycarbonate Front Windshield

Provides optical grade, fretted anti-glare tinted and anti-scratch coated polycarbonate front upper windshield, lower left and right window panels. Each panel is individually serviceable and will provide improved impact resistance from falling debris in various applications such as waste, recycling, forestry and agriculture while allowing unobstructed visibility to the ground and work tool.








Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	562-5684	
924K, 930K, 938K	PWR, RHN, SWL		Recommended Dealer
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT	302-3004	Install

Windshield Guard


Provides protection to the front windshield from falling debris in any application, while allowing excellent visibility to the ground and work tool.




Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	387-4190	1.5 Hour
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

Power Train Lower Guard

Provides lower transmission guard that mounts underneath the rear frame.






Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	374-5844	0.5 Hour
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

Power Train Side Guard

Provides two (2) side transmission guards that mount to both sides of the rear frame.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	452-0857	
924K, 930K, 938K	PWR, RHN, SWL		0.25 Hour
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT	374-5866	

Rear Radiator Guard

Provides protection to the rear of the machine and cooling package. Includes swing out guard for cooling access and mounting for rear camera. Kit is not available on any 924K and 926M models.






Model	Serial Number Prefix	Part Number	Estimated Install Time	
930M	F5K, HEY, J5K, KTG	377-4109*		
930K	RHN		- 3.0 Hours	
930K	FRK, P3K, EYE			
938M	J3R, P5K	377-1573*		
938K	SWL			
938K	REP, W8K, XXT			

^{*}Cannot be used when machine is equipped with certain regional roading regulations packages. Contact your Cat® dealer for further information.

Steering Cylinder Guard


Provides protection to both steering cylinders, preventing damage to rods and cylinder seals.



Model	Serial Number Prefix	Part Number	Estimated Install Time	
926M, 930M	LTE, W5L, F5K, HEY, J5K, KTG			
924K, 930K	PWR, RHN	377-1594		
924K, 930K	HJF, KW4, SNZ, EYE, FRK, P3K		1.0 Hour	
938M	J3R, P5K			
938K	SWL	387-4194		
938K	REP, W8K, XXT			

Tilt Cylinder Guard (High Lift)

Provides protection to the tilt cylinder, preventing damage to the rod, hoses and cylinder seal. Cannot be used with endorsed check valve option. For high lift linkage machines only.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M	LTE, W5L		
924K	PWR	437-1879	
924K	HJF, KW4, SNZ		0 E Hour
930M, 938M	F5K, HEY, J5K, KTG, J3R, P5K		0.5 Hour
930K, 938K	RHN, SWL	437-1881	
930K, 938K	EYE, FRK, P3K, REP, W8K, XXT		

Tilt Cylinder Guard (Standard Lift)

Provides protection to the tilt cylinder, preventing damage to the rod, hoses and cylinder seal. Cannot be used with endorsed check valve option. For standard lift linkage machines only.




Model	Serial Number Prefix	Part Number	Estimated Install Time	
926M	LTE	437-1878		
924K	PWR			
924K	HJF, KW4, SNZ			
926M	W5L	583-6242	0.5 Hour	
930M, 938M	F5K, HEY, J5K, KTG, J3R, P5K			
930K, 938K	RHN, SWL	437-1880		
930K, 938K	EYE, FRK, P3K, REP, W8K, XXT			

MAINTENANCE AND IMPROVEMENT

Cab Air Filter (RESPA)

Provides a powered cab air pre cleaner and filter, mounting brackets, and interior cab pressure sensor. Improves operator air quality and cab pressurization. Recommended for high debris environments.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	376-5324	Recommended Dealer Install
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		motun

Precleaner

Provides turbine precleaner for the engine that ejects particles before intake. Recommended for high debris environments.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	376-4390	0.25 Hour
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

Fuel Door

Provides an elevated fuel fill location along with an access door for fueling the machine through the large right-side service door without opening it.






Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	418-4190	1.0 Hour
924K, 930K, 938K	PWR, RHN, SWL		

PERFORMANCE AND PRODUCTIVITY

Alternator, Heavy Duty


This filtered and brushless alternator, 150 amp, is ideal for very dusty or corrosive environments or applications such as waste, agriculture, construction, demolition, or any high debris environments.




Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	387-4189	Recommended Dealer Install
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		motun

Autolube

Provides automatic lubrication of machine pin joints requiring daily lubrication: Linkage pin joints, including bucket pins, articulation hitch, steering cylinders and rear axle trunnions. System is accessed through the secondary display to adjust lubrication frequency and provide low reservoir alert. Kit is compatible with both standard and high lift machine configurations.







Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE**, W5L**, F5K**, J5K**, KTG**, J3R**, P5K**	522-0264*	Recommended Dealer
924K, 930K, 938K	KW4**, SNZ, FRK, P3K**, REP, W8K**		Install


^{*}Requires Cat Electronic Technician (ET) to complete installation of this kit.


 $[\]ensuremath{^{**}}\xspace$ Applicable only to machines within the following serial number range:

Model	Serial Number Range	
926M	LTE03500-LTE99999, W5L00100-W5L99999	
930M	F5K00110-F5K99999, J5K00115-J5K99999, KTG03000-KTG99999	
938M	J3R03650-J3R99999, P5K00100-P5K99999	
924K	KW401100-KW499999	
930K	P3K00500-P3K99999	
938K	3K W8K00900-W8K99999	

Axle Breather

Provides remote mounted breathers for both axles and hystat gearbox, used when machines enter deep water.







Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938N	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	419-7164	Recommended Dealer
930K	RHN		Install
924K, 930K, 938K	KW4, SNZ, EYE, FRK, P3K, REP, W8K		

Block Heater – 120V

Provides 120V block heater to improve cold start performance.









Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	374-5855*	2.0 Hours
924K, 930K, 938K	PWR, RHN, SWL		
924K, 930K, 938K	KW4, SNZ, FRK, P3K, REP, W8K		

^{*}For regions with 120V power.

Block Heater – 240V

Provides 240V block heater to improve cold start performance.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	374-5856*	2.0 Hours
924K, 930K, 938K	KW4, SNZ, FRK, P3K, REP, W8K		
924K, 930K, 938K	HJF, EYE, XXT	363-6402*	

^{*}For regions with 240V power.

Ether Aid

Provides ether starting aid to improve cold start performance.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	374-5854	0.5 Hour
924K, 930K, 938K	SNZ, FRK, REP		
924K, 930K, 938K	HJF, KW4, EYE, P3K, XXT, W8K	430-2919	

Heavy Duty Starting

Provides battery box for installation of two additional batteries (in place of standard toolbox), along with cables and battery tie-downs. Batteries not included.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M	LTE, W5L, F5K, HEY, J5K, KTG		
924K, 930K	PWR, RHN	370-7007	
924K, 930K	HJF, KW4, SNZ, EYE, FRK, P3K		3.0 Hours
938M	J3R, P5K		3.0 nours
938K	SWL	370-7010	
938K	REP, W8K, XXT		

Cat® Production Measurement (CPM)

Includes sensors and hardware. Software license for CPM will be a separate charge. Requires secondary display and Product Link Elite (Network Manager). 250 hours of demonstration time can be activated via the secondary display and will remind the operator when time is near expiration. Requires purchase of software license from https://fps.cat.com (Use Reason Code #149). Requires software, 518-3210, for permanent activation.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE**, W5L**, F5K**, HEY, J5K**, KTG**, J3R**, P5K**	494-7950*	Recommended Dealer
924K, 930K, 938K	KW4**, SNZ, FRK, P3K**, REP, W8K**		Install


^{*}Requires Cat Electronic Technician (ET) to complete installation of this kit.


^{**}Applicable only to machines within the following serial number range:

Model	Serial Number Range	
926M	LTE03500-LTE99999, W5L00100-W5L99999	
930M	F5K00110-F5K99999, J5K00115-J5K99999, KTG03000-KTG99999	
938M	J3R03650-J3R99999, P5K00100-P5K99999	
924K	KW401100-KW499999	
930K	P3K00500-P3K99999	
938K	W8K00900-W8K99999	

CPM Printer

Includes a printer for onboard ticket printing capability for Cat Production Measurement (CPM) system. Printer mounts in rear right corner of cab.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE**, W5L**, F5K**, HEY, J5K**, KTG**, J3R**, P5K**	494-8001*	Recommended Dealer
924K, 930K, 938K	KW4**, SNZ, FRK, P3K**, REP, W8K**		Install

^{*}Requires Cat Electronic Technician (ET) to complete installation of this kit.

^{**}Applicable only to machines within the following serial number range:

Model	Serial Number Range	
926M	LTE03500-LTE99999, W5L00100-W5L99999	
930M	F5K00110-F5K99999, J5K00115-J5K99999, KTG03000-KTG99999	
938M	J3R03650-J3R99999, P5K00100-P5K99999	
924K	KW401100-KW499999	
930K	P3K00500-P3K99999	
938K	W8K00900-W8K99999	

Counterweight, Heavy

Provides additional frame mounted counterweights +320 kg (705 lb). Kit converts standard counterweight group to heavy.



Model	Serial Number Prefix	Part Number	Estimated Install Time
930M, 938M	F5K, KTG, J3R, P5K		
930K, 938K	RHN, SWL	374-5858	1.0 Hour
930K, 938K	EYE, FRK, P3K, REP, W8K, XXT		

Counterweight, Aggregate


Converts a heavy counterweight machine to a Logger/Aggregate counterweight machine by additional frame mounted counterweight for use in applications such as Log and Lumber, Aggregate Handling, Auto Re-Handling and heavy material handling. Not recommended for general construction machines. Not compatible for High Lift Linkage configurations. CANNOT BE USED WITH: Flexport or Brawler Tires.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, KTG, J3R, P5K	467 7000	1.0 Hour
924K, 930K, 938K	SNZ, FRK, P3K, REP, W8K	467-7992	

Dual Mode Steering (Quick Steer)

Provides Dual Mode Hand Metering Unit (HMU) and required lines to convert a standard steering machine into Dual Mode. Adds the ability to enable Dual Mode Steering (Quick Steer) to minimize operator efforts in repetitive cycles.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M	LTE*, W5L*, F5K*, HEY*, J5K*, KTG*	387-4185	Recommended Dealer
924K, 930K	PWR, RHN		
924K, 930K	HJF, SNZ, KW4, EYE, FRK, P3K	377-4199	
938M	J3R*, P5K*	207 4100	Install
938K	SWL	387-4186	
938K	W8K	377-4200	

^{*}Applicable only to machines within the following serial number range:

Model	Serial Number Range	
926M	LTE06550-LTE99999, W5L00100-W5L99999	
930M	F5K00110-F5K99999, HEY00550-HEY99999, J5K00115-J5K99999, KTG06550-KTG99999	
938M	J3R07425-J3R99999, P5K00120-P5K99999	

Product Link Elite Network Manager

Includes Network Manager for conversion of Product Link Pro to Product Link Elite. Required to field install Cat® Production Measurement kit, 494-7590. Availability varies by country.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	494-8000	Recommended Dealer
924K, 930K, 938K	KW4*, SNZ, FRK, P3K*, REP, W8K*		Install

^{*}Applicable only to machines within the following serial number range:

Model	Serial Number Range
924K	KW401100-KW499999
930K	P3K00500-P3K99999
938K	W8K00900-W8K99999

Quick Coupler Disconnects

Provides a set (male and female) of flat face, connect under pressure quick disconnects. Recommended to adapt existing work tools to the new improved small wheel loader quick disconnects.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE*, W5L, F5K*, HEY, J5K*, KTG, J3R*, P5K		
924K, 930K, 938K	PWR, RHN, SWL	441-4005	1.0 Hour
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

 $^{{}^*\!\}mathsf{Applicable}$ only to machines within the following serial number range:

Model	Serial Number Range	
926 M	LTE00001-LTE06549	
930M	F5K00110-F5K99999, J5K00115-J5K99999	
938M	J3R00001-J3R07424	

Quick Coupler, Cast Fusion

Provides an electro-hydraulic, cast fusion interface coupler actuation system activated from the cab. Includes constant pressure coupler wedges. Requires machine to be equipped with coupler valve and hydraulic lines. Recommended to install Counterweight, Heavy.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M	LTE**, W5L**, F5K**, HEY**, J5K**, KTG**	566-5497*	1.5 Hours
924K, 930K	SNZ**, FRK**		
938M	J3R**, P5K**	566-5498*	
938K	REP**	300-3498*	


^{*}Requires Cat Electronic Technician (ET) to complete installation of this kit.

^{**}Applicable only to machines within the following serial number range:

Model	Serial Number Range	
926M	LTE06550-LTE99999, W5L00100-W5L99999	
930M	F5K00110-F5K99999, HEY00550-HEY99999, J5K00115-J5K99999, KTG05000-KTG99999	
938M	J3R07425-J3R99999, P5K00120-P5K99999	
924K	SNZ00950-SNZ99999	
930K	FRK00775-FRK99999	
938K	REP00900-REP99999	

Quick Coupler, Fabricated Fusion

Provides an electro-hydraulic coupler actuation system activated from the cab. Includes constant pressure coupler wedges. Requires machine to be equipped with coupler valve and hydraulic lines. Recommend to also install Counterweight, Heavy.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M	LTE**, HEY**, KTG**	374-5790*	1 F Hours
924K, 930K	SNZ, KW4, FRK, P3K		
938M	J3R**	274 F701*	1.5 Hours
938K	REP, W8K	374-5791*	

^{*}Requires Cat Electronic Technician (ET) to complete installation of this kit.

^{**}Applicable only to machines within the following serial number range:

Model	Serial Number Range	
926M	LTE00001-LTE06549	
930M	HEY00001-HEY00549, KTG00001-KTG04999	
938M	J3R00001-J3R7424	

Quick Coupler, Cast ISO

Provides an electro-hydraulic cast ISO interface coupler actuation system activated from the cab. Includes lock valve cylinder. Compatible with many competitive work tools, ISO standard coupler interface is also used by Volvo. Requires machine to be equipped with coupler valve and hydraulic lines. Recommend to also install Counterweight, Heavy.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M	LTE**, W5L**, F5K**, HEY**, J5K**, KTG**	566-5499*	2.0 Hours
924K, 930K	SNZ**, FRK**		
938M	J3R**	545-5499*	
938K	W8K		
938M	J3R***, P5K***	566-5500*	
938K	REP***		

^{*}Requires Cat Electronic Technician (ET) to complete installation of this kit.

^{**}Applicable only to machines within the following serial number range:


Model	Serial Number Range	
926 M	LTE06550-LTE99999, W5L00100-W5L99999	
930M	F5K00110-F5K99999, HEY00550-HEY99999, J5K00115-J5K99999, KTG05000-KTG99999	
938M	J3R00001-J3R07424	
924K	SNZ00950-SNZ99999	
930K	FRK00775-FRK99999	

 $[\]ensuremath{^{***}}\xspace$ Applicable only to machines within the following serial number range:

Model	Serial Number Range	
938M	J3R07425-J3R99999, P5K00120-P5K99999	
938K	REP00900-REP99999	

Quick Coupler, ISO

Provides an electro-hydraulic Cast ISO interface coupler actuation system activated from the cab. Includes lock valve cylinder. Compatible with many competitive work tools, ISO standard coupler interface is also used by Volvo. Requires machine to be equipped with coupler valve and hydraulic lines. Recommended to install Counterweight, Heavy.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M	LTE**, HEY**, KTG**	F4F F400*	2.0.110
926K, 930K	KW4, P3K	545-5498*	2.0 Hours


^{*}Requires Cat Electronic Technician (ET) to complete installation of this kit.


^{**}Applicable only to machines within the following serial number range:

Model	Serial Number Range	
926M	LTE06551-LTE99999	
930M	HEY00001-HEY00549, KTG00001-KTG49999	

Coupler Ready

Provides coupler valve and hydraulic lines to convert a two valve, pin-on, standard lift machine into a two valve, coupler ready machine.





Model	Serial Number Prefix	Part Number	Estimated Install Time
924K	HJF, KW4, SNZ	447-4892	
926M, 930M	LTE*, HEY*, KTG*		
924K, 930K	PWR, RHN	447-4893	
930K	EYE, FRK, P3K		December 1 December 1
938M	J3R*		Recommended Dealer Install
938K	SWL	447-4895	
938K	REP, W8K, XXT		
926M, 930M, 938M	LTE**, W5L**, F5K**, HEY**, J5K**, KTG**, J35**, P5K**	576-4833	

^{*}Applicable only to machines within the following serial number range:


Model	Serial Number Range	
926M	LTE00001-LTE06549	
930M	HEY00001-HEY00549, KTG00001-KTG04999	
938M	J3R00001-J3R07424	

^{**}Applicable only to machines within the following serial number range:

Model	Serial Number Range	
926M	LTE06550-LTE99999, W5L00100-W5L99999	
930M	F5K00110-F5K99999, HEY00550-HEY99999, J5K00115-J5K99999, KTG05000-KTG99999	
938M	J3R07425-J3R99999, P5K00120-P5K99999	

Fusion Hook, Flat Back

Provides brackets with fusion hooks on the back and a flat interface on the front allowing it to be welded to existing small wheel loader work tools. Recommended for customers who want to re-hinge existing non-fusion tools or competitive tools to a fusion interface.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		Recommended Dealer
924K, 930K, 938K	PWR, RHN, SWL	371-2400	Install
924K, 930K, 938K	HJF, KW4, EYE, P3K, W8K, XXT		

Fusion/IT Adapter


Provides brackets with fusion hooks on the back and a flat interface on the front allowing it to be welded to existing small wheel loader work tools. Recommended for customers who want to re-hinge existing non-fusion tools or competitive tools to a fusion interface.




Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	589-6664	
924K, 930K, 938K	PWR, RHN, SWL	277 4140	0.25 Hour
924K, 930K, 938K	HJF, KW4, EYE, P3K, W8K, XXT	377-4149	

Reversing Fan

Provides a hydraulically operated demand fan with reversing option. Includes automatic and manual controls for fan reversal. Recommended for applications with a high content of airborne debris.






Model	Serial Number Prefix	Part Number	Estimated Install Time
924K, 930K	PWR, RHN	207 4102	
924K, 930K, 938K	HJF, EYE, XXT	387-4182	
938K	SWL	387-4183	Recommended Dealer Install
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K	452.0050	instan
924K, 930K, 938K	SNZ, KW4, FRK, P3K, REP, W8K	452-0858	

^{*}Part numbers are for reference only

Ride Control

Provides multi-accumulator ride control system to absorb shock and reduce machine bounce when traveling, resulting in a more comfortable ride and better material retention.



Model	Serial Number Prefix	Part Number	Estimated Install Time
926M	LTE**, W5L**	577-0372*	
926M	LTE	452-0855*	
930M, 938M	HEY**, KTG**, J3R**	4E2 00E6*	
930K, 938K	FRK, P3K**, REP, W8K**	452-0856*	Recommended Dealer
930M, 938M	F5K***, HEY***, J5K***, KTG***, J3R***, P5K***	577-0373*	Install
938K	SWL	274 5052*	
938K	XXT	374-5853*	

^{*}Requires Cat Electronic Technician (ET) to complete installation of this kit.

^{**}Applicable only to machines within the following serial number range:

Model	Serial Number Range	
926 M	LTE06550-LTE99999, W5L00100-W5L99999	
930M	HEY00001-HEY00550, KTG00001-KTG04999	
938M	J3R00001-J3R07424	
938K	P3K00001-P3K00999, W8K00001-W8K01999	


 $[\]ensuremath{^{***}}\xspace$ Applicable only to machines within the following serial number range:

Model	Serial Number Range
930M	F5K00110-F5K99999, HEY00550-HEY99999, J5K00115-J5K99999, KTG05000-KTG99999
938M	J3R07425-J3R99999, P5K00120-P5K99999

Fourth Valve Auxiliary Hydraulic System

Provides implement valve section, joystick, Electronic Control Module (ECM) and hydraulic lines to convert a three valve (3V) machine to four valve (4V).





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M	LTE*, HEY*, KTG*	452 0062	
924K, 930K	SNZ, KW4*, FRK, P3K*	452-0862	
926M, 930M	LTE**, W5L**, F5K**, HEY**, J5K**, KTG**	576-9770	
938M	J3R*	452-0863	Recommended Dealer Install
938K	W8K*	402-0003	
938M	J3R**, P5K**	F77 0271	
938K	W8K**	577-0371	

^{*}Applicable only to machines within the following serial number range:


Model	Serial Number Range
926M	LTE00001-LTE06549
930M	HEY00001-HEY00550, KTG00001-KTG04999
938M	J3R00001-J3R07424
924K	KW400130-KW499999
930K	P3K00140-P3K99999
938K	W8K00900-W8K01999


^{**}Applicable only to machines within the following serial number range:


Model	Serial Number Range
926M	LTE06550-LTE99999, W5L00100-W5L99999
930M	F5K00110-F5K99999, HEY00550-HEY99999, J5K00115-J5K99999, KTG05000-KTG99999
938M	J3R07425-J3R99999, P5K00120-P5K99999
938K	W8K02000-W8K99999

Third and Fourth Valve Auxiliary Hydraulic System, Standard Lift

Provides implement valve section, joystick and hydraulic lines to convert a two valve (2V) standard lift machine to four valve (4V).








Model	Serial Number Prefix	Part Number	Estimated Install Time
924K	KW4*	569-8604	Recommended Dealer Install

^{*}Applicable only to machines within the following serial number range:

Model	Serial Number Range
924K	KW400130-KW499999

Third Function Coupler Jumper Lines

Provides third function jumper lines and threaded flat face connect under pressure quick disconnects mounted to the coupler. Recommended for use with third function work tools.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE*, HEY*, KTG*, J3R*		
924K, 930K, 938K	PWR, RHN, SWL	441-3368	
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT	777 0000	1.0 Hour
926M, 930M, 938M	LTE**, W5L**, F5K**, HEY**, J5K**, KTG**, J3R**, P5K**	576-9758	

^{*}Applicable only to machines within the following serial number range:


Model	Serial Number Range
926M	LTE00001-LTE06549
930M	HEY00001-HEY00550, KTG00001-KTG04999
938M	J3R00001-J3R07424

^{**}Applicable only to machines within the following serial number range:

Model	Serial Number Range
926M	LTE06550-LTE99999, W5L00100-W5L99999
930M	F5K00110-F5K99999, HEY00550-HEY99999, J5K00115-J5K99999, KTG05000-KTG99999
938M	J3R07425-J3R99999, P5K00120-P5K99999

Third Valve Auxiliary Hydraulic System, High Lift

Provides implement valve section, joystick and hydraulic lines to convert a two valve (2V) high lift machine to three valve (3V).






Model	Serial Number Prefix	Part Number	Estimated Install Time
926M	LTE*	420 4221	
924K	PWR	420-4331	
930M	KTG*	420 4222	Decembered of Declar Install
930K	RHN	420-4333	Recommended Dealer Install
938M	J3R*	420 4225	
938K	SWL	420-4335	


^{*}Applicable only to machines within the following serial number range:

Model	Serial Number Range
926M	LTE00001-LTE06549
930M	KTG00001-KTG04999
938M	J3R00001-J3R07424

Third Valve Auxiliary Hydraulic System, Standard Lift

Provides implement valve section, joystick and hydraulic lines to convert a two valve (2V) standard lift machine to three valve (3V).





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M	LTE*, KTG*		
924K, 930K	PWR, RHN	387-4021	
930K	EYE, FRK]	
926M, 930M	LTE**, W5L**, F5K**, HEY**, J5K**	577-0374	
938M	J3R*		
938K	SWL	387-4023	
938K	REP, XXT]	Recommended Dealer Install
938M	J3R**, P5K**	577-0375	
924K	KW4*, SNZ	452-0864	
926M, 930M	LTE***, KTG***	F07.0400	
930K	P3K*	527-8436	
938M	J3R***	F07 0407	
938K	W8K***	527-8437	

(continued on next page)

Third Valve Auxiliary Hydraulic System, Standard Lift (continued)

*Applicable only to machines within the following serial number range:

Model	Serial Number Range
926M	LTE00001-LTE03499
930M	KTG00001-KTG02999
938M	J3R00001-J3R03649
924K	KW400130-KW499999
938K	P3K00500-P3K99999

^{**}Applicable only to machines within the following serial number range:

Model	Serial Number Range		
926M	LTE06550-LTE99999, W5L00100-W5L99999		
930M	F5K00110-F5K99999, HEY00550-HEY99999, J5K00115-J5K99999, KTG05000-KTG99999		
938M	J3R07425-J3R99999, P5K00120-P5K99999		


^{***}Applicable only to machines within the following serial number range:

Model	Serial Number Range		
926M	LTE03500-LTE06549		
930M	KTG03000-KTG04999		
938M	J3R03650-J3R07424		
938K	W8K00900-W8K99999		

SECURITY

Machine Security System (MSS)

Kit provides a programmable system to manage access to machine. Includes two special MSS keys.





Model	Serial Number Prefix	Part Number	Estimated Install Time
926M, 930M, 938M	LTE, W5L, F5K, HEY, J5K, KTG, J3R, P5K		
924K, 930K, 938K	PWR, RHN, SWL	370-7004*	Recommended Dealer Install
924K, 930K, 938K	HJF, KW4, SNZ, EYE, FRK, P3K, REP, W8K, XXT		

^{*}This kit has software enabled features that must be activated by a Cat dealer.

NOTES

